



# 42BYGHW

**AP&S**  
MOTORREDUCTORES

Posibles aplicaciones:

Peso:



## Características

Model	Step angle (°)	Motor Length L(mm)	Rate Voltage (V)	Rate Current (A)	Phase Resistance (Ω)	Phase Inductance (mH)	Holding Torque (g.cm)	Lead Wire (NO.)	Rotor Inertia (g.cm <sup>2</sup> )	Detent Torque (g.cm)	Motor Weight (kg)
42BYGHW205	1.8	34	12	0.3	40	18	1200	6	34	200	0.2
42BYGHW208	1.8	34	12	0.4	30	35	3200	4	35	160	0.2
42BYGHW213	1.8	34	12	0.6	20	15	2000	5	34	200	0.2
42BYGHW602	1.8	40	12	0.4	30	21	2500	6	54	220	0.30
42BYGHW603	1.8	40	12	0.4	30	40	4000	4	54	220	0.30
42BYGHW607	1.8	40	3.84	1.2	3.2	2.8	4000	6	54	220	0.30
42BYGHW609	1.8	40	2.55	1.7	1.5	2.8	4000	4	54	220	0.30
42BYGHW801	1.8	48	12	0.4	30	25	4800	6	68	280	0.37
42BYGHW804	1.8	48	3.6	1.2	3.0	5	4800	4	68	260	0.37
42BYGHW811	1.8	48	3.1	2.5	1.25	1.8	4800	4	68	280	0.37

## Dimensiones

